Epoxy.com Product #702

Delineator &Traffic Marker & Dowel Bar and Anchor Bolt Adhesive

DESCRIPTION

PRODUCT #702 Delineator & Traffic Marker and Anchor Bolt Adhesive is a two component, 1:1 ratio, 100% solids, moisture insensitive epoxy resin system manufactured to bond delineators and traffic markers to median barriers, parapets, and roadways. **Epoxy.com PRODUCT #702** is a normal setting adhesive for use in temperatures above 50° F. **PRODUCT #702** will bond to steel, concrete, and asphalt. **Epoxy.com PRODUCT #702** exceeds the requirements of AASHTO M237 Type IV.

ADVANTAGES

PRODUCT #702 is conveniently manufactured in a 1:1 mix ratio, for easy mixing and proportioning. One part of **Epoxy.com Product #75** Filler may be added by volume for economy, when setting roadway traffic markers.

PHYSICAL PROPERTIES

Color "A" Component	White
Color "B" Component	Black
Color Mixed Material	Gray
Consistency Mixed Material	Paste
Gel Time Minimum	10 minutes at 75° F
	60 grams (neat)
Set Time Maximum	2 hours
Bond Strength ASTM C882,	2 hour 450 p.s.i
	24 hours 1800 p.s.i*
Shelf Life	2 years

^{*} Gel Time and Bond Strength results comply with AASHTO M237 Type IV

PACKAGING

PRODUCT #702 is available in 2 gallon, 10 gallon and 100 gallon units.

COVERAGE

When used neat, a 2-gallon unit of **Epoxy.com PRODUCT #702** will cover approximately 100 square feet at a 15 mil thickness. When used as a mortar, a 2-gallon unit of **PRODUCT #702** mixed with 2 gallons by volume of **PRODUCT #75** Filler will yield approximately 785 cubic inches of mortar.

SURFACE PREPARATION

For best results, areas to receive **Epoxy.com PRODUCT #702** should be free of laitance, grease, oil, and any other contaminants, which would inhibit bond. Sandblasting, waterblasting, or wire brushing for surface preparation are recommended.

MIXING

Mix **PRODUCT** #702 for approximately 3 minutes in a clean pail, using a slow speed drill and an **Epoxy.com-Mixing Paddle**. To obtain a mortar, add **Product** #75 **Filler** slowly while continuing to mix. **Epoxy.com PRODUCT** #702 may be used with automatic dispensing equipment utilizing a static mixer head. Heating the material will lower viscosity to allow easier placement. Heating will speed set time and cure.

COVERAGE:

There are 231 cubic inches to a gallon. So you will get about 25.6 square feet per 1/16 inch of thickness. If using this as an anchor bolt, or dowel bar adhesive, you can double check you volume with the Epoxy.com Dowel Bar and Anchor Bolt Adhesive Calculator.

NOTES:

LIMITATIONS

Epoxy.com PRODUCT #702 should not be used when surface temperatures are below 40 ° F.

CAUTIONS

"A" Component: WARNING! Contains epoxy resin. May cause skin sensitization or other allergic responses. Avoid inhalation of vapor. Use good ventilation, particularly if material is heated or sprayed. Prevent contact with skin or eyes. If skin is contacted, wash immediately with soap and water. If eyes are contacted, flush immediately with water and consult a physician.

"B" Component: WARNING! Contains amine polymer. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Call a physician. Wash clothing before reuse. Discard contaminated shoes.

WEAR PROTECTIVE CLOTHING, GOGGLES, GLOVES, AND/OR BARRIER CREAMS!

FOR INDUSTRIAL USE ONLY KEEP AWAY FROM CHILDREN

For more information please contact:

Epoxy.com. 352-489-1666 (Phone) 352-465-3497 (Fax) info@epoxy.com www.epoxy.com

Epoxy.com a division of Epoxy Systems, Inc. warrants its products (when properly stored) for the period of time as follows: Epoxies, Product #315, Product #315BC, and Product #316 one (1) year; Polyesters, Methyl Methacrylates (normal) two (2) months and Polyurethanes Four (4) months; Power Tools and Equipment 90 days; Vinyl Esters, High Molecular Weight Methacrylates (HMMA) and all other resins (not specifically mentioned above) 30 days; hand tools (non-power tools) 30 days. Epoxy.com warrants that its products will be free of manufacturing defects and will be in conformity with published specifications when handled, stored, mixed and applied in accordance with recommendations of Epoxy.com. If any product fails to meet this warranty, the liability of Epoxy.com will be limited to replacement of any non-conforming material if notice of such non-conformity is given to Epoxy.com within the warranty period for the material (as indicated above), or within 1 year of the delivery of materials (whichever is sooner). Epoxy.com may in its discretion refund the price received by Epoxy.com in lieu of replacing the material. No customer, distributor, or representative of Epoxy.com is authorized to change or modify the published specifications of this warranty in any way. No one is authorized to make oral warranties on behalf of Epoxy.com. In order to obtain replacement or refund the customer must provide written notice containing full details of the non-conformity. Epoxy.com reserves the right to inspect the non-conforming material prior to replacement. EXCEPT FOR THE EXPRESSED WARRANTY STATED ABOVE, THERE ARE NO OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR PURPOSE. Epoxy.com 'S OBLIGATION SHALL NOT EXTEND BEYOND THE OBLIGATIONS EXPRESSLY UNDERTAKEN ABOVE AND Epoxy.com SHALL HAVE NO LIABILITY OR RESPONSIBILITY TO THE PURCHASER OR ANY THIRD PARTY FOR ANY LOSS, COST, EXPENSE, DAMAGE OR LIABILITY, WHETHER DIRECT OR INDIRECT, OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. All quotes and sales subject to availability.

Many of our products are made on an individual order basis. Unless authorized in writing by Epoxy.com a division of Epoxy Systems, Inc. in writing before the material is made, there are no returns on items purchased from us, once the order has been processed, and the material made. In the event of authorized returns a restocking charge will be charged in the amount of 30% of the value of the material returned or \$150 whichever is greater. No returns on non-list priced items. All Returns are for merchandise (store) credit only, no cash or credit card credits. In the event of a return, buyer is responsible for the cost of shipping and handling in both directions.